# 450 SERIES

ARTICULATING BOOM LIFT



## **Performance**

45 ft	13.72 m
30 ft	9.14 m
25 ft	7.62 m
24 ft	7.3 m
355 Degrees Non-Continuous	
550 lb	250 kg
30 x 72 in.	0.76 x 1.83 m
180 Degrees Hydraulic	
4 ft 1 in.	1.24 m
145 Degrees (+76, -69)	
15,850 lb	7,190 kg
12,650 lb	5,738 kg
65 psi	4.57 kg/cm <sup>2</sup>
4.25 mph	6.84 km/hr
30%	
45%	
4 in.	10 cm
6 ft 9 in.	2.06 m
15 ft 8 in.	4.78 m
	30 ft 25 ft 24 ft 355 Degrees Non-Continu 550 lb 30 x 72 in. 180 Degrees Hydraulic 4 ft 1 in. 145 Degrees (+76, -69) 15,850 lb 12,650 lb 65 psi 4.25 mph 30% 45% 4 in. 6 ft 9 in.

# **Standard Specifications**

#### Power Source

Standard

Optional

Power Jource			
Dual Fuel Engine Kubota WG2503 Diesel Engine	61 hp	45.5 kW	
Deutz D2.9 L4 Tier 4 Final	49 hp	36.4 kW	
Fuel Tank Capacity	16 gal.	60.6 L	
Hydraulic System			
System Capacity	38 gal.	143.8 L	
Tank Capacity	36 gal.	136.27 L	
Auxiliary Power	12V-DC		
Tires			

Foam-filled Tires

Non-marking Tires

33/1550 x 16.5 Pneumatic Lug Tread



# **Standard Features**

- 4 ft 1 in. (1.24 m) Articulating Jib
- Platform 30 x 72 in. (0.76 x 1.83 m) Side Entry
- 180 Degree Hydraulic Platform Rotator
- Platform Console Machine Status Light Panel<sup>1</sup>
- 110V-AC Receptacle in the Platform • 5 Degree Tilt Alarm/Indicator Light
- Swing Out Engine Module
- Improved Multi-Function Controls
- Gull-Wing Turntable Hoods
- 12V-DC Auxiliary Power

- Hourmeter
- Interactive Display at Ground Controls
- Proportional Controls
- Control ADE® System
- Lifting/Tie Down Lugs
- Horn
- Four-Wheel Hydrostatic Drive
- Oscillating Axle
- Cast Aluminum Control Box
- Motion Alarm
- Reduced Time to Full Height

## **Accessories & Options**

- 30 x 60 in. (0.76 x 1.25 m) Platform
- Inward Self-Closing Swing
- 36 x 72 in. (0.91 x 1.83 m) Platform
- Fall Arrest Platform 30 x 60 in. (.76 x 1.53 m)
- Mesh to Top Rail Bolt-on Aluminum
- 1/2 in. Air Line to Platform
- Soft Touch System
- · AC Generator
- · Flashing Amber Beacon
- 43.5 lb (19.73 kg) Propane Tank

- Cold Weather Kit<sup>2</sup>
- Arctic Package4
- Hostile Environment Kit<sup>3</sup>
- · Light Package
- · Platform Worklights
- Operator Tool Trav
- Accessory Packages
  - SkyPower® Package
     SkyWelder® Package
  - SkyGuard®
  - PipeRack
- 1. Provides indicator lights at platform control console for system distress, low fuel, 5 degree tilt light, and foot switch status.
- Includes battery blanket, hydraulic tank heater, block heater (GM), glow plugs (Deutz).
   Includes boom wipers, cylinder bellows and console cover.
   Includes sarctic hydraulic hoses (drive and steer only) and main boom cable, extreme cold engine oil, fuel conditioner, engine block heater, battery blanket, glow plugs, hydraulic tank heater, and oversized footswitch

Note: Some options may increase lead time, and some option combinations may not be available.

# **450 SERIES**


ARTICULATING BOOM LIFT




#### **Dimensions**

All dimensions are approximate.

#### 450A






# 7ft5.3 in. (2.27 m) (6.4 in. (41.7 cm)


7 ft 9 in.

(2.36 m)




#### **Reach Diagrams**

#### 450A



#### 450AJ





### The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.



#### JLG Industries, Inc.

1 JLG Drive McConnellsburg, PA 17233-9533 Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT Fax 717-485-6417

www.jlg.com

**An Oshkosh Corporation Company**